

2.2 Thin-wall heat shrink tubing

H-2(3X) - Thin-wall heat shrink tubing - 3:1 - Operating temperature up to 125 °C



Technical specifications

Brand	: WKK (produced by Hongshang)
Shrink ratio	: 3:1
Flame retardant	: Yes
Self-extinguishing	: Yes
Adhesive	: No
Operating temperature	: -55 °C up to +125 °C
Minimum shrink temperature	: +70 °C
Minimum full recovery temperature	: +110 °C
Longitudinal change	: 0 up to 10% max.
Material	: Crosslinked polyolefin
Halogen-free	: No
Approvals	: UL E204071, CSA, RoHS
Available colors	: Black (UV resistant)= White= Red= Blue= Yellow= Green= Purple= Brown= Orange= Grey=

Scan this QR code for article numbers, current prices and stock information and to order directly.

Type / Size	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Packaging type			
				Reel (meter)	Minibox (meter)	Length piece (mm)	
H-2(3X) 1.5/0.5	1.5	0.5	0.45	150	10	1.000	1.220
H-2(3X) 3.0/1.0	3.0	1.0	0.50	150	10	1.000	1.220
H-2(3X) 4.5/1.5	4.5	1.5	0.60	75	10	1.000	1.220
H-2(3X) 6.0/2.0	6.0	2.0	0.65	75	10	1.000	1.220
H-2(3X) 9.0/3.0	9.0	3.0	0.75	75	5	1.000	1.220
H-2(3X) 12.0/4.0	12.0	4.0	0.80	50	5	1.000	1.220
H-2(3X) 18.0/6.0	18.0	6.0	0.90	30	5	1.000	1.220
H-2(3X) 24.0/8.0	24.0	8.0	1.00	30	5	1.000	1.220
H-2(3X) 39.0/13.0	39.0	13.0	1.20	30	-	1.000	1.220