

Technical Datasheet

tasker® C402 – 2x2x0,22 mm²

Single Shielded Multipair Audio Cable



CATEGORY Multipair Audio Cable (See Audio Catalogue)
APPLICATIONS Audio Mixers, Benches and Audio Balanced multi sockets.

- A:** Black Soft **PVC** Sheath.
Outer cable Diam. Ø 9,00 (±0,20) mm.
- B:** The single pair are isolated with black **PVC**, numbered from one to the number of elements and wrapped together with polyester base tape.
Nom. Ø 3,00 (±0,20) mm.
- C:** The single pair are shielded with spiral in O.F.C. red copper, covering 100% + tinned copper Drain Wire.
- D:** The single cores are insulated with **Solid PE**, colored one Yellow and one Transparent, and wrapped with not weaved polyester base tape.
Nom. Ø 1,00 (±0,20) mm.
- E:** O.F.C. red copper formation 28x0,10 mm.
Nom. Cross section 2x2x0,22 mm².

MARKING **tasker®** C402 2x2x22 mm² PROFESSIONAL MULTIPAIR CABLE FOR AUDIO MIXER MADE IN ITALY

CUSTOM PRODUCTION This product may be custom produced also in **LSZH** polymer, **PE**, **PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	79,15 Ω/Km
Capacity Core/Core	75 pF/m
Capacity Core/Shield	160 pF/m
Velocity of Propagation	66%
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 24.06.19
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			10% measurement tolerance, unless otherwise indicated